

572153

SHAVER SOCKET 120-230V WH



Mechanisms supplied with rocker plates, to be equipped with surround plate.

Support frame not needed.

Conform to BS EN 61558-2-5. IP 24.

For use with European, British, American, Australian 2-pin plugs.

Screwless live and neutral terminals.

Double wound isolating transformer.

Automatic self-resetting overload feature.

Plug insertion operates micro-switch which energises transformer.

To be equipped with 2 gang - 3 module surround plate.

Power supply : 230 V - 50/60 Hz.

3 modules.

Technical

Finish	White
For	Use with European, British, American, Australian 2-pin plugs. For flush mounting boxes, use BS 2 gang box depth 48 mm, US type, Italian type boxes depth 48 mm.
Information	To be equipped with BS 2 gang - 3 module plates
Installation	For flush mounting boxes, use BS 2 gang box depth 48 mm.
IP Rating	IP24
Power supply	230 V - 50/60 Hz
Standards	BS EN 61558-2-5

Datasheet generated from <https://onetimepim.com> last updated Monday, October 26, 2020 9:36:44 AM

572653

SHAVER SOCKET 120-230V MG



Mechanisms supplied with rocker plates, to be equipped with surround plate.

Support frame not needed.

Conform to BS EN 61558-2-5. IP 24.

For use with European, British, American, Australian 2-pin plugs.

Screwless live and neutral terminals.

Double wound isolating transformer.

Automatic self-resetting overload feature.

Plug insertion operates micro-switch which energises transformer.

To be equipped with 2 gang - 3 module surround plate.

Power supply : 230 V - 50/60 Hz.

3 modules.

Technical

Finish	Magnesium
For	Use with European, British, American, Australian 2-pin plugs. For flush mounting boxes, use BS 2 gang box depth 48 mm, US type, Italian type boxes depth 48 mm.
Information	To be equipped with BS 2 gang - 3 module plates
Installation	For flush mounting boxes, use BS 2 gang box depth 48 mm.
IP Rating	IP24
Power supply	230 V - 50/60 Hz
Standards	BS EN 61558-2-5

Datasheet generated from <https://onetimepim.com> last updated Monday, October 26, 2020 9:36:46 AM