

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Switch for household and similar fixed-electrical installation

Name and address of the applicant

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - FRANCE

Name and address of the manufacturer

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - FRANCE

Name and address of the factory

See Annex

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

Series : ARTEOR
References of switches : see annex
(References of accessories: see test report n° 154281-718095A)

Additional information (if necessary may also be reported on page 2)

Supersedes CBTC FR 578292/M2 dated 06/12/2016. Update further to the evolution of the standard(s) and addition of product references

 Additional Information on page 2


A sample of the product was tested and found to be in conformity with

IEC 60669-1:2017

As shown in the Test Report Ref. No. which forms part of this Certificate

87006-578294/1 to 87006-578294/8, 111914-622443, 154281-718095A, 154281-718095B

This CB Test Certificate is issued by the National Certification Body

LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 20/02/2019

Signature: **Jean-François BRUEL**
Certification Officer

ANNEX

Name and address of the factories:


LEGRAND (BEIJING) ELECTRICAL Co Ltd
N° 4 CHAOQIAN ROAD, CHANGPING DISTRICT KEJIYUANQU
101214 BEIJING
CHINA

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX
FRANCE

NOVATEUR ELECTRICAL & DIGITAL SYSTEMS PRIVATE LTD
A-2, SINNAR – MALEGAON VILLAGE MIDC,
NASHIK PUNE ROAD, DIST : NASHIK,
STATE - MAHARASHTRA
INDIA - 422113



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 20/02/2019


Signature: **Jean-François BRUEL**
Certification Officer

ANNEX (Continued)

Reference								Rated values	Pattern	Actuating	Module	Specificities
Square				Round								
champagne	Soft alu	White	Magnesium	champagne	Soft alu	White	Magnesium					
		5 720 15	5 725 15					6A-250V~	1	RM	1	Bell symbol
		5 720 56	5 725 26			5 730 80	5 731 80	6A-250V~	1	RM	2	Bell symbol
5 700 00	5 710 00	5 720 00	5 725 00					6A-250V~	1	RM	1	
						5 730 00	5 731 00	6A-250V~	1	RM	1 left	
		5 730 01	5 731 01					6A-250V~	1	RM	1 centre	
						5 730 02	5 731 02	6A-250V~	1	RM	1 right	
		5 720 16	5 725 16					6A-250V~	1	RM	1	Pilot light
		5 720 30	5 725 30			5 730 50	5 731 50	6A-250V~	1	RM	2	
		5 720 01	5 725 01					6A-250V~	6	RM	1	
		5 732 96	5 737 96			5 732 97	5 737 97	6A-250V~	6	RM	1+1	Marking bed light
		5 733 84	5 738 84			5 733 85	5 738 85	6A-250V~	6	RM	1+1	Marking desk light + entrance light
		5 720 31	5 725 31			5 730 51	5 731 51	6A-250V~	6	RM	2	
		5 732 86	5 737 86			5 732 87	5 737 87	6A-250V~	6	RM	2	Marking light
		5 720 02	5 725 02					6A-250V~	6	RM	1	Pilot light
		5 720 32	5 725 32			5 730 52	5 731 52	6A-250V~	6	RM	2	Pilot light
		5 720 03	5 725 03					6A-250V~	6	RM	1	Label holder
5 700 33	5 710 33	5 720 33	5 725 33			5 730 53	5 731 53	6A-250V~	6	RM	2	Label holder
		5 720 40	5 725 40			5 730 65	5 731 65	10AX-250V~	2	R	2	
		5 720 38	5 725 38			5 730 63	5 731 63	10AX-250V~	7	R	2	
5 700 34	5 710 34	5 720 34	5 725 34	5 700 66	5 710 66	5 730 60	5 731 60	10AX-250V~	1	R	2	
5 700 04	5 710 04	5 720 04	5 725 04					10AX-250V~	1	R	1	
				5 700 62	5 710 62	5 730 10	5 731 10	10AX-250V~	1	R	1 left	
		5 730 11	5 731 11					10AX-250V~	1	R	1 centre	



LCIE – Laboratoire Central des Industries Electriques
 33, avenue du Général Leclerc – BP8
 FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 20/02/2019


 Signature: **Jean-François BRUEL**
 Certification Officer

ANNEX (Continued)

Reference								Rated values	Pattern	Actuating	Module	Specificities
Square				Round								
champagne	Soft alu	White	Magnesium	champagne	Soft alu	White	Magnesium					
				5 700 63	5 710 63	5 730 12	5 731 12	10AX-250V~	1	R	1 right	
		5 724 50						10AX-250V~	1	R	1	red actuator
5 700 35	5 710 35	5 720 35	5 725 35	5 700 67	5 710 67	5 730 61	5 731 61	10AX-250V~	6	R	2	
5 700 05	5 710 05	5 720 05	5 725 05					10AX-250V~	6	R	1	
		5 732 94	5 737 94			5 732 95	5 737 95	10AX-250V~	6	R	1+1	marking bed light
		5 733 82	5 738 82			5 733 83	5 738 83	10AX-250V~	6	R	1+1	marking desk light + entrance light
		5 720 54	5 725 54			5 720 74	5 725 74	10AX-250V~	6	R	1+1	marking do not disturb + Please clean up
				5 700 64	5 710 64	5 730 13	5 731 13	10AX-250V~	6	R	1 left	
		5 730 14	5 731 14					10AX-250V~	6	R	1 centre	
				5 700 65	5 710 65	5 730 15	5 731 15	10AX-250V~	6	R	1 right	
		5 720 06	5 725 06					10AX-250V~	6	R	1	pilot light
		5 720 36	5 725 36			5 730 62	5 731 62	10AX-250V~	6	R	2	pilot light
		5 720 37	5 725 37					10AX-250V~	6	R	2	pilot light + label holder
						5 730 16	5 731 16	10AX-250V~	6	R	1 left	pilot light
		5 730 17	5 731 17					10AX-250V~	6	R	1 centre	pilot light
						5 730 18	5 731 18	10AX-250V~	6	R	1 right	pilot light
		5 720 48	5 725 48			5 730 77	5 731 77	20AX-250V~	6/2	R	2	
		5 732 84	5 737 84			5 732 85	5 737 85	20AX-250V~	6/2	R	2	marking light
		5 720 46	5 725 46			5 730 75	5 731 75	20AX-250V~	2	R	2	
		5 720 47	5 725 47			5 730 76	5 731 76	20AX-250V~	2	R	2	pilot light
		5 720 49	5 725 49			5 730 78	5 731 78	20AX-250V~	2	R	2	pilot light + marking "Water heater"



LCIE – Laboratoire Central des Industries Electriques
 33, avenue du Général Leclerc – BP8
 FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 20/02/2019


 Signature: **Jean-François BRUEL**
 Certification Officer

ANNEX (Continued)

Reference								Rated values	Pattern	Actuating	Module	Specificities
Square				Round								
champagne	Soft alu	White	Magnesium	champagne	Soft alu	White	Magnesium					
5 700 09	5 710 09	5 720 09	5 725 09					20AX-250V~	1	R	1	
						5 730 20	5 731 20	20AX-250V~	1	R	1 left	
		5 730 21	5 731 21					20AX-250V~	1	R	1 centre	
						5 730 22	5 731 22	20AX-250V~	1	R	1 right	
		5 720 41	5 725 41			5 730 70	5 731 70	20AX-250V~	1	R	2	
		5 720 43	5 725 43			5 730 72	5 731 72	20AX-250V~	1+1+1	R	2	
5 700 10	5 710 10	5 720 10	5 725 10					20AX-250V~	6	R	1	
						5 730 23	5 731 23	20AX-250V~	6	R	1 left	
		5 730 24	5 731 24					20AX-250V~	6	R	1 centre	
						5 730 25	5 731 25	20AX-250V~	6	R	1 right	
		5 720 11	5 725 11					20AX-250V~	6	R	1	pilot light
						5 730 26	5 731 26	20AX-250V~	6	R	1 left	pilot light
		5 730 27	5 731 27					20AX-250V~	6	R	1 centre	pilot light
						5 730 28	5 731 28	20AX-250V~	6	R	1 right	pilot light
		5 720 42	5 725 42			5 730 71	5 731 71	20AX-250V~	6	R	2	pilot light
		5 720 44	5 725 44			5 730 73	5 731 73	20AX-250V~	6+1+6	R	2	
		5 720 50	5 725 50					20A-250V~	3	R	2	
5 700 54	5 710 54	5 722 20	5 727 20			5 732 20	5 737 20	10AX-250V~	6+6	R	2	for rolling shutter
		5 732 22	5 737 22			5 732 23	5 737 23	10AX-250V~	6+6	R	2	for rolling shutter with marking
		5 732 34	5 737 34			5 732 35	5 737 35	10AX-250V~	6+6	R	2	for curtain with marking
		5 722 19	5 727 19			5 732 19	5 737 19	6A-250V~	6+6	RM	2	for rolling shutter
		5 732 24	5 737 24			5 732 25	5 737 25	6A-250V~	6+6	RM	2	for rolling shutter with marking
		5 732 36	5 737 36			5 732 37	5 737 37	6A-250V~	6+6	RM	2	for curtain with marking



LCIE – Laboratoire Central des Industries Electriques
 33, avenue du Général Leclerc – BP8
 FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 20/02/2019

 Signature: **Jean-François BRUEL**
 Certification Officer

ANNEX (End)

Reference								Rated values	Pattern	Actuating	Module	Specificities
Square				Round								
champagne	Soft alu	White	Magnesium	champagne	Soft alu	White	Magnesium					
		5 722 17	5 727 17					10A-250V~	3X1	Rot	2	Mini gap for ventilation


RM: Rocker momentary
R: Rocker
Rot: Rotary

CHARACTERISTICS OF APPLIANCE

pattern number	see tables
contacts opening (gap)	normal gap - mini gap for 5 722 17 - 5 727 17
degree of protection	IP 20 - IP 44 with cover plate 5 751 90
method of actuating	Rocker- momentary contact - rotary see tables
method of mounting	flush type
method of installation	design A
type of terminals	screw type
rated current (A) or (AX)	see tables
Rated voltage	250V~



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 20/02/2019

Signature: **Jean-François BRUEL**
Certification Officer