

NANOPOWER SERIES

1500VA Line Interactive UPS



A Line Interactive UPS is a type of Uninterruptible Power Supply (UPS) that provides backup power to electronic devices such as computers, servers, and telecommunication hardware for a few minutes in case of power outages. It gives stable output using an automatic voltage stabilizer to regulate the voltage levels and prevent damage from low or high voltages.



General Features

- Line Interactive UPS with simulated sinewave output
- Excellent microprocessor control guarantees high reliability (Internal self-diagnostic technology)
- Boost and buck AVR for voltage stabilization (one boost and one buck control)
- Auto restart while AC is recovering
- Cold start function
- Off-mode charging
- Fast intelligent battery recharge function
- Offering LED and LCD panels for selections
- Optional Generator compatible
- Optional USB/RS232 communication port and RJ11/RJ45 protection

SPECIFICATIONS

MODEL		CN1500N / CN1500N-LU
Capacity	VA	1500
	Watts	900
Input	Voltage	220/230/240Vac
	Voltage Range	162~290Vac
	Frequency Range	60/50Hz (auto sensing)
Output	AC Voltage Regulation (Batt. Mode)	±10%
	Frequency Range (Batt. Mode)	60/50Hz ±1 Hz
	Transfer Time	Typical 2-6ms, 10ms Max.
	Waveform (Batt. Mode)	Simulated Sinewave
	Output Socket Quantity	IEC - C13 - 6nos / Universal (Customizable) - 4nos
Battery	Battery Voltage	24Vdc
	Battery Type & Number	12 V /9 Ah x 2
	Typical Recharge Time	6~8 hours recover to 90% capacity
Indicators	LED Display (LED version)	AC Mode, Battery Mode, Overload, Fault
	LCD Display (LCD version)	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Battery Low
Protection	Full Protection	Short circuit, Overload , Overcharge and over discharge protection
Alarm	Battery mode	Sounding every 10 seconds
	Low Battery	Sounding every second
	Overload	Sounding every 0.5 second
	Battery Replacement Alarm	Sounding every 2 seconds
	Fault	Continuously sounding
Management	Communication port	USB or RS232(Supports Windows® 7/8/10, Linux, Unix, and MAC)
Operating Environment	Humidity	0-90 % RH @ 0- 40°C (non-condensing)
Physical	Noise Level	Less than 55dB
	IP Rating	IP 20
	Dimension W x D x H (mm)	380x158x198
	Net Weight S/H (kg)	10.1 (Approx.)
	Safety	CE; IEC/EN 62040-1; IEC/EN 60950-1
Performance	EMC	IEC/EN 62040-2; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8
	Performance	IEC/EN 62040-3

*Product specifications and appearances are subject to change without prior notice.

NANOPOWER SERIES

1500VA Line Interactive UPS



ORDERING INFORMATION

Part Number	Description
CN1500N	1500VA Line Interactive UPS (Internal Battery)
CN1500N-LU	1500VA Line Interactive UPS with LCD display and USB Port(Internal Battery)

