

NANOPOWER SERIES

2400VA Line Interactive UPS



A Line Interactive UPS is a type of Uninterruptible Power Supply (UPS) that provides backup power to electronic devices such as computers, servers, and telecommunication hardware for a few minutes in case of power outages. It uses an inverter output and an automatic voltage stabilizer to regulate the voltage levels and prevent damage from low or high voltages.



General Features

- Line Interactive UPS with simulated sinewave output
- Excellent microprocessor control guarantees high reliability (Internal self-diagnostic technology)
- Boost and buck AVR for voltage stabilization (one boost and one buck control)
- Auto restart while AC is recovering
- Cold start function
- Off-mode charging
- Fast intelligent battery recharge function
- Offering LED and LCD panels for selections
- Optional Generator compatible
- Optional USB/RS232 communication port and RJ11/RJ45 protection

SPECIFICATIONS

MODEL		CN2400N / CN2400N-LU
Capacity	VA	2400
	Watts	1440
Input	Voltage	220/230/240Vac
	Voltage Range	162~290Vac
	Frequency Range	60/50Hz (auto sensing)
Output	AC Voltage Regulation (Batt. Mode)	±10%
	Frequency Range (Batt. Mode)	60/50Hz ±1 Hz
	Transfer Time	Typical 2-6ms, 10ms Max.
	Waveform (Batt. Mode)	Simulated Sinewave
Battery	Battery Voltage	48Vdc
	Battery Type & Number	12 V / 7Ah x 4
	Typical Recharge Time	6~8 hours recover to 90% capacity
Indicators	LED Display (LED version)	N/A
	LCD Display (LCD version)	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Battery Low
Protection	Full Protection	Short circuit, Overload, Overcharge and over discharge protection
Alarm	Battery mode	Sounding every 10 seconds
	Low Battery	Sounding every second
	Overload	Sounding every 0.5 second
	Battery Replacement Alarm	Sounding every 2 seconds
	Fault	Continuously sounding
Management	Communication port	USB or RS232 (Supports Window 2000/2003/XP/Vista/2008, Window 7, Linux, Unix, and MAC)
Operating Environment	Humidity	0-90 % RH @ 0- 40°C (non-condensing)
	Noise Level	Less than 55dB
Physical	Dimension, W x D x H (mm)	433x144x207
	Net Weight S/H (kg)	Approx.20

STANDARDS		
Safety	IEC/EN62040-1; IEC/EN60950-1	
EMC	IEC/EN62040-2; IEC61000-4-2; IEC61000-4-3; IEC61000-4-5; IEC61000-4-6; IEC61000-4-8	
Performance	IEC/EN62040-3	

NANOPOWER SERIES

2400VA Line Interactive UPS



ORDERING INFORMATION

Part Number	Description
CN2400N	2400VA Line Interactive UPS (Internal Battery)
CN2400N-LU	2400VA Line Interactive UPS with LCD display and USB Port(Internal Battery)

