

CAT. N° 4 196 61



MCB RX³ 4500 - 1P - 230/400 V~ - 6 A - C CURVE

Pack (number of units)	12
Volume (dm ³)	2,012
Weight (g)	1 566,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 196 62


MCB RX³ 4500 - 1P - 230/400 V~ - 10 A - C CURVE


Pack (number of units)	12
Volume (dm ³)	2,076
Weight (g)	1 559,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 64


MCB RX³ 4500 - 1P - 230/400 V~ - 16 A - C CURVE


Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 224,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 66


MCB RX³ 4500 - 1P - 230/400 V~ - 25 A - C CURVE


Pack (number of units)	12
Volume (dm ³)	2,018
Weight (g)	1 607,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 65

**MCB RX³ 4500 - 1P - 230/400 V~ - 20 A - C CURVE**


Pack (number of units)	12
Volume (dm ³)	2,018
Weight (g)	1 579,00

Product characteristics**Single pole 230/400 V~**

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 1

General characteristics**MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve**

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 67


MCB RX³ 4500 - 1P - 230/400 V~ - 32 A - C CURVE


Pack (number of units)	12
Volume (dm ³)	2,012
Weight (g)	1 688,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 68


MCB RX³ 4500 - 1P - 230/400 V~ - 40 A - C CURVE

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 690,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 196 69


MCB RX³ 4500 - 1P - 230/400 V~ - 50 A - C CURVE


Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 767,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 70


MCB RX³ 4500 - 1P - 230/400 V~ - 63 A - C CURVE


Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 763,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating I_n : 63 A
- Number of modules : 1

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 199 46



MCB RX³ 4500 - 1P+N 230 V~ - 6 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm ³)	1,633
Weight (g)	1 049,00

Product characteristics

Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - 670457](#)

Installation & technical data

- [F02068EN-00](#)

Environmental product profile

- [Environnemental product sheet n°8 E0037C-EN](#)

CAT. N° 4 199 47



MCB RX³ 4500 - 1P+N 230 V~ - 10 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm ³)	1,633
Weight (g)	1 044,00

Product characteristics

Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - 670457](#)

Installation & technical data

- [F02068EN-00](#)

Environmental product profile

- [Environnemental product sheet n°8 E0037C-EN](#)

CAT. N° 4 199 49



MCB RX³ 4500 - 1P+N 230 V~ - 16 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm ³)	1,633
Weight (g)	1 062,00

Product characteristics

Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - 670457](#)

Installation & technical data

- [F02068EN-00](#)

Environmental product profile

- [Environnemental product sheet n°8 E0037C-EN](#)

CAT. N° 4 199 50



MCB RX³ 4500 - 1P+N 230 V~ - 20 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm ³)	1,633
Weight (g)	1 073,00

Product characteristics

Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating In : 20 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - 670457](#)

Installation & technical data

- [F02068EN-00](#)

Environmental product profile

- [Environnemental product sheet n°8 E0037C-EN](#)

CAT. N° 4 199 51



MCB RX³ 4500 - 1P+N 230 V~ - 25 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm ³)	1,633
Weight (g)	1 096,00

Product characteristics

Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - 670457](#)

Installation & technical data

- [F02068EN-00](#)

Environmental product profile

- [Environnemental product sheet n°8 E0037C-EN](#)

CAT. N° 4 199 52



MCB RX³ 4500 - 1P+N 230 V~ - 32 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm ³)	1,633
Weight (g)	1 122,00

Product characteristics

Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 1

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [QC / CB - 670457](#)



Installation & technical data

- [F02068EN-00](#)



Environmental product profile

- [Environnemental product sheet n°8 E0037C-EN](#)

CAT. N° 4 196 94



MCB RX³ 4500 - 2P - 230/400 V~ - 6 A - C CURVE

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 562,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 2

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 196 95


MCB RX³ 4500 - 2P - 230/400 V~ - 10 A - C CURVE


Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 231,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 97


MCB RX³ 4500 - 2P - 230/400 V~ - 16 A - C CURVE


Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 561,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 196 98



MCB RX³ 4500 - 2P - 230/400 V~ - 20 A - C CURVE

Pack (number of units)	6
Volume (dm ³)	2,012
Weight (g)	1 583,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 2

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 196 99


MCB RX³ 4500 - 2P - 230/400 V~ - 25 A - C CURVE

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 614,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 00


MCB RX³ 4500 - 2P - 230/400 V~ - 32 A - C CURVE


Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 679,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 197 01


MCB RX³ 4500 - 2P - 230/400 V~ - 40 A - C CURVE


Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 679,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 197 02


MCB RX³ 4500 - 2P - 230/400 V~ - 50 A - C CURVE

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 763,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 03


MCB RX³ 4500 - 2P - 230/400 V~ - 63 A - C CURVE

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 773,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 63 A
- Number of modules : 2

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 05



MCB RX³ 4500 - 3P 400 V~ - 6 A - C CURVE

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 564,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 3

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 06


MCB RX³ 4500 - 3P 400 V~ - 10 A - C CURVE


Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 224,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 3

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 197 08


MCB RX³ 4500 - 3P 400 V~ - 16 A - C CURVE


Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 225,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 3

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 197 09


MCB RX³ 4500 - 3P 400 V~ - 20 A - C CURVE

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 576,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 3

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 10


MCB RX³ 4500 - 3P 400 V~ - 25 A - C CURVE

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 606,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 3

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 11



MCB RX³ 4500 - 3P 400 V~ - 32 A - C CURVE

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 680,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 3

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 12



MCB RX³ 4500 - 3P 400 V~ - 40 A - C CURVE

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 686,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 3

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 13



MCB RX³ 4500 - 3P 400 V~ - 50 A - C CURVE

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 763,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 3

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 14


MCB RX³ 4500 - 3P 400 V~ - 63 A - C CURVE


Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 815,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 63 A
- Number of modules : 3

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

 **Installation & technical data**

- [F01911EN-01](#)

CAT. N° 4 197 38


MCB RX³ 4500 - 4P 400 V~ - 6 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 559,00

Product characteristics
4-pole 400 V~

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 4

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 39



MCB RX³ 4500 - 4P 400 V~ - 10 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 486,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 4

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 41



MCB RX³ 4500 - 4P 400 V~ - 16 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 561,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 4

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 42


MCB RX³ 4500 - 4P 400 V~ - 20 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 577,00

Product characteristics
4-pole 400 V~

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 4

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 43



MCB RX³ 4500 - 4P 400 V~ - 25 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 619,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 4

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 44



MCB RX³ 4500 - 4P 400 V~ - 32 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 682,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 4

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [CEBEC - 20022](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)



Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 45


MCB RX³ 4500 - 4P 400 V~ - 40 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 702,00

Product characteristics
4-pole 400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 4

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 46


MCB RX³ 4500 - 4P 400 V~ - 50 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 769,00

Product characteristics
4-pole 400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 4

General characteristics
MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)


Installation & technical data

- [F01911EN-01](#)

CAT. N° 4 197 47



MCB RX³ 4500 - 4P 400 V~ - 63 A - C CURVE

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 767,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 63 A
- Number of modules : 4

General characteristics

MCBs RX³ 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 4500 - IEC 60898-1 - 230/400 V~
 - 4.5 kA - IEC 60947-2 - 230/400 V~
 - 6000 - IEC 60898-1 - 127/220 V~
 - 6 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [OC / CB - IT 16504](#)
- [VDE - 40042042](#)
- [VDE - 40044433](#)

Installation & technical data

- [F01911EN-01](#)