

CAT. N° 4 191 99



MCB RX³ 6000 - 1P - 230/400 V~ - 6 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 543,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 00



MCB RX³ 6000 - 1P - 230/400 V~ - 10 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 519,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 01



MCB RX³ 6000 - 1P - 230/400 V~ - 13 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 528,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 13 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 02



MCB RX³ 6000 - 1P - 230/400 V~ - 16 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 525,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 03



MCB RX³ 6000 - 1P - 230/400 V~ - 20 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 564,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 04



MCB RX³ 6000 - 1P - 230/400 V~ - 25 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 653,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 05



MCB RX³ 6000 - 1P - 230/400 V~ - 32 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 685,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 06



MCB RX³ 6000 - 1P - 230/400 V~ - 40 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 722,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 07



MCB RX³ 6000 - 1P - 230/400 V~ - 50 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 773,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 08



MCB RX³ 6000 - 1P - 230/400 V~ - 63 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 774,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 63 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 198 37



MCB RX³ 6000 - 1P - 230/400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	2,012
Weight (g)	1 571,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 38



MCB RX³ 6000 - 1P - 230/400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	2,012
Weight (g)	1 570,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 40



MCB RX³ 6000 - 1P - 230/400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 567,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 41



MCB RX³ 6000 - 1P - 230/400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	2,018
Weight (g)	1 569,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 42



MCB RX³ 6000 - 1P - 230/400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	2,012
Weight (g)	1 664,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 43



MCB RX³ 6000 - 1P - 230/400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	2,012
Weight (g)	1 796,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 44



MCB RX³ 6000 - 1P - 230/400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 601,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 45



MCB RX³ 6000 - 1P - 230/400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 769,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 46



MCB RX³ 6000 - 1P - 230/400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	12
Volume (dm ³)	1,864
Weight (g)	1 768,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 1

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 192 21



MCB RX³ 6000 - 2P - 230/400 V~ - 6 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 519,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 6 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 22



MCB RX³ 6000 - 2P - 230/400 V~ - 10 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 519,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 23



MCB RX³ 6000 - 2P - 230/400 V~ - 13 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 522,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 13 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 24



MCB RX³ 6000 - 2P - 230/400 V~ - 16 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 527,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 25



MCB RX³ 6000 - 2P - 230/400 V~ - 20 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 557,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 26



MCB RX³ 6000 - 2P - 230/400 V~ - 25 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 643,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 25 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 27



MCB RX³ 6000 - 2P - 230/400 V~ - 32 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 683,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 28



MCB RX³ 6000 - 2P - 230/400 V~ - 40 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 723,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 29



MCB RX³ 6000 - 2P - 230/400 V~ - 50 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 771,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 50 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 30



MCB RX³ 6000 - 2P - 230/400 V~ - 63 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 780,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating I_n : 63 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 198 70



MCB RX³ 6000 - 2P - 230/400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 562,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 71



MCB RX³ 6000 - 2P - 230/400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 563,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 73



MCB RX³ 6000 - 2P - 230/400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 563,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

REF . 4 198 74


MCB RX³ 6000 - 2P - 230/400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS



Emballage (nombre number of units)	6
Volume (dm ³)	1,864
Poids (g)	1 573,00

Caractéristiques du produit
2-pole 230/400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 2

Caractéristiques générales
MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation associée
 **Catalogue pages & additional information**

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

 **Installation & technical data**

- [F01910EN-01](#)

CAT. N° 4 198 75



MCB RX³ 6000 - 2P - 230/400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 618,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 76


MCB RX³ 6000 - 2P - 230/400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 684,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating I_n : 32 A
- Number of modules : 2

General characteristics
MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)


Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 77

**MCB RX³ 6000 - 2P - 230/400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS**

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 680,00

Product characteristics**2-pole 230/400 V~**

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 2

General characteristics**MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve**

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation**Catalogue pages & additional information**

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

**Agreements & certificates of conformity**

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

**Installation & technical data**

- [F01910EN-01](#)

CAT. N° 4 198 78



MCB RX³ 6000 - 2P - 230/400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 767,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 79



MCB RX³ 6000 - 2P - 230/400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	6
Volume (dm ³)	1,864
Weight (g)	1 770,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 2

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 192 32



MCB RX³ 6000 - 3P 400 V~ - 6 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 518,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 33



MCB RX³ 6000 - 3P 400 V~ - 10 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 519,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 34


MCB RX³ 6000 - 3P 400 V~ - 13 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 525,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 13 A
- Number of modules : 3

General characteristics
MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)


Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 35


MCB RX³ 6000 - 3P 400 V~ - 16 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS


Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 525,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 3

General characteristics
MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

 **Installation & technical data**

- [F01909EN-02](#)

CAT. N° 4 192 36



MCB RX³ 6000 - 3P 400 V~ - 20 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	2,694
Weight (g)	1 564,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [IMQ - IT-14270](#)
- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 37



MCB RX³ 6000 - 3P 400 V~ - 25 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 648,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 38


MCB RX³ 6000 - 3P 400 V~ - 32 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 684,00

Product characteristics
3-pole 400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 3

General characteristics
MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)


Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 39



MCB RX³ 6000 - 3P 400 V~ - 40 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 723,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 40



MCB RX³ 6000 - 3P 400 V~ - 50 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 785,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 41



MCB RX³ 6000 - 3P 400 V~ - 63 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 777,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [QC / CB - IT-14270](#)
- [VDE - 40041249](#)
- [IMQ - IT-14270](#)

Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 198 81



MCB RX³ 6000 - 3P 400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 559,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 82



MCB RX³ 6000 - 3P 400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 566,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 84



MCB RX³ 6000 - 3P 400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 561,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 85



MCB RX³ 6000 - 3P 400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 577,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 86



MCB RX³ 6000 - 3P 400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 615,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 87



MCB RX³ 6000 - 3P 400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 675,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 88

**MCB RX³ 6000 - 3P 400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS**

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 686,00

Product characteristics**3-pole 400 V~**

- C curve
- Nominal rating In : 40 A
- Number of modules : 3

General characteristics**MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve**

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation**Catalogue pages & additional information**

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

**Agreements & certificates of conformity**

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

**Installation & technical data**

- [F01910EN-01](#)

CAT. N° 4 198 89



MCB RX³ 6000 - 3P 400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 773,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 198 90



MCB RX³ 6000 - 3P 400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	4
Volume (dm ³)	1,864
Weight (g)	1 774,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 3

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 192 55



MCB RX³ 6000 - 4P 400 V~ - 10 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	2,012
Weight (g)	1 542,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 10 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 56



MCB RX³ 6000 - 4P 400 V~ - 13 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	2,012
Weight (g)	1 551,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 13 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 57



MCB RX³ 6000 - 4P 400 V~ - 16 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	2,012
Weight (g)	1 548,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 16 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 192 58



MCB RX³ 6000 - 4P 400 V~ - 20 A - C CURVE - PRONG/FORK TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	2,012
Weight (g)	1 578,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 20 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Installation & technical data

- [F01909EN-02](#)

CAT. N° 4 199 14



MCB RX³ 6000 - 4P 400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 564,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 15



MCB RX³ 6000 - 4P 400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 565,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 17



MCB RX³ 6000 - 4P 400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 563,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 18



MCB RX³ 6000 - 4P 400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 580,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 19



MCB RX³ 6000 - 4P 400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 616,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 20



MCB RX³ 6000 - 4P 400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 683,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [OC / CB - IT21483](#)
- [VDE - 40042228](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 21



MCB RX³ 6000 - 4P 400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 684,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 40 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 22



MCB RX³ 6000 - 4P 400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 769,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation



Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)



Installation & technical data

- [F01910EN-01](#)

CAT. N° 4 199 23



MCB RX³ 6000 - 4P 400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	3
Volume (dm ³)	1,864
Weight (g)	1 797,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 4

General characteristics

MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
 - 10000 - IEC 60898-1 - 127/220 V~
 - 10 kA - IEC 60947-2 - 127/220 V~

Documentation

Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40042228](#)
- [OC / CB - IT21483](#)

Installation & technical data

- [F01910EN-01](#)