

CAT. N° 0 490 40



## CONNECTED THERMOSTAT SMARTHER WITH NETATMO SURFACE MOUNTING - 2 ON/OFF CONTROL OUTPUTS - WHITE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	1,127
Weight (g)	178,00

### Product characteristics

#### Smarter with Netatmo connected thermostat

- Can be controlled locally, remotely or using voice control (via a voice assistant)
- Requires a Wi-Fi router and Internet access
- Control:
  - remotely via the Home + Control app by Legrand (latest version of iOS required for iPhone, iPad, iPod. Android 5.0 minimum required)
  - using voice control via Apple Siri, Amazon Alexa or Google Assistant
- Works with all types of domestic boiler (burning wood, oil or gas) and with heat pumps, compatible with over 1500 boilers
- Functions:
  - Auto-Adapt integrates the weather and the house's thermal characteristics to ensure the desired temperature is achieved
  - Schedule: saves energy by only heating the house when needed.
 Activation of Away and Frost guard modes in cases of extended absence via the Home + Control App
  - View history to monitor and optimise your energy consumption
- Can be used in conjunction with Additional Smart Thermostatic Heads Cat.No NAV-PRO
- Range up to 100 m (868 MHz)
- Measurement temperature: 0°C to 50°C, accuracy +/- 0.1°C. Setpoint temperature: 5°C to 30°C, with adjustment +/- 0.5°C
- Compatible with: Wi-Fi 802.11 b/g/n (2.4 GHz)
- Security supported: Open/WEP/WPA/WPA-2 personal (TKIP and AES)

#### For surface mounting

- 2 on/off control outputs: 230 VA, volt-free contact, low voltage contact, valves (4 A - 256 VA max) for simultaneous management of summer/winter modes
- 230 V~ mains supply
- White

### General characteristics

#### Connected home - connected thermostats

- Products available from a connected Authorised Dealer

### Documentation

#### Agreements & certificates of conformity

- Decl. UE RED - 70 354 01

CAT. N° 0 490 40

#### ELIOT PROGRAMME



Eliot Programme by Legrand for connected objects

CAT. N° 0 490 39



## CONNECTED THERMOSTAT SMARTER WITH NETATMO FLUSH MOUNTING - 1 ON/OFF CONTROL OUTPUT - BLACK

Pack (number of units)	1
Volume (dm <sup>3</sup> )	1,127
Weight (g)	232,00

### Product characteristics

#### Smarter with Netatmo connected thermostat

- Can be controlled locally, remotely or using voice control (via a voice assistant)
- Requires a Wi-Fi router and Internet access
- Control:
  - remotely via the Home + Control app by Legrand (latest version of iOS required for iPhone, iPad, iPod. Android 5.0 minimum required)
  - using voice control via Apple Siri, Amazon Alexa or Google Assistant
- Works with all types of domestic boiler (burning wood, oil or gas) and with heat pumps, compatible with over 1500 boilers
- Functions:
  - Auto-Adapt integrates the weather and the house's thermal characteristics to ensure the desired temperature is achieved
  - Schedule: saves energy by only heating the house when needed.
 Activation of Away and Frost guard modes in cases of extended absence via the Home + Control App
  - View history to monitor and optimise your energy consumption
- Can be used in conjunction with Additional Smart Thermostatic Heads Cat.No NAV-PRO
- Range up to 100 m (868 MHz)
- Measurement temperature: 0°C to 50°C, accuracy +/- 0.1°C. Setpoint temperature: 5°C to 30°C, with adjustment +/- 0.5°C
- Compatible with: Wi-Fi 802.11 b/g/n (2.4 GHz)
- Security supported: Open/WEP/WPA/WPA-2 personal (TKIP and AES)

#### For flush mounting

- 1 on/off control output: 230 VA, volt-free contact, low-voltage contact, valves (4 A - 256 VA max)
- 230 V~ mains supply
- 2 modules
- Black

### General characteristics

#### Connected home - connected thermostats

- Products available from a connected Authorised Dealer

### Documentation



#### Agreements & certificates of conformity

- Decl. UE RED - 70 354 01

CAT. N° 0 490 39

#### ELIOT PROGRAMME



Eliot Programme by Legrand for connected objects

CAT. N° 0 490 38



## CONNECTED THERMOSTAT SMARTHER WITH NETATMO FLUSH MOUNTING - 1 ON/OFF CONTROL OUTPUT - WHITE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	1,127
Weight (g)	234,00

### Product characteristics

#### Smarter with Netatmo connected thermostat

- Can be controlled locally, remotely or using voice control (via a voice assistant)
- Requires a Wi-Fi router and Internet access
- Control:
  - remotely via the Home + Control app by Legrand (latest version of iOS required for iPhone, iPad, iPod. Android 5.0 minimum required)
  - using voice control via Apple Siri, Amazon Alexa or Google Assistant
- Works with all types of domestic boiler (burning wood, oil or gas) and with heat pumps, compatible with over 1500 boilers
- Functions:
  - Auto-Adapt integrates the weather and the house's thermal characteristics to ensure the desired temperature is achieved
  - Schedule: saves energy by only heating the house when needed.
 Activation of Away and Frost guard modes in cases of extended absence via the Home + Control App
  - View history to monitor and optimise your energy consumption
- Can be used in conjunction with Additional Smart Thermostatic Heads Cat.No NAV-PRO
- Range up to 100 m (868 MHz)
- Measurement temperature: 0°C to 50°C, accuracy +/- 0.1°C. Setpoint temperature: 5°C to 30°C, with adjustment +/- 0.5°C
- Compatible with: Wi-Fi 802.11 b/g/n (2.4 GHz)
- Security supported: Open/WEP/WPA/WPA-2 personal (TKIP and AES)

#### For flush mounting

- 1 on/off control output: 230 VA, volt-free contact, low-voltage contact, valves (4 A - 256 VA max)
- 230 V~ mains supply
- 2 modules
- White

### General characteristics

#### Connected home - connected thermostats

- Products available from a connected Authorised Dealer

### Documentation



#### Agreements & certificates of conformity

- Decl. UE RED - 70 354 01

CAT. N° 0 490 38

#### ELIOT PROGRAMME



Eliot Programme by Legrand for connected objects