

CAT. N° 4 115 02



RCCB TX³ - 2P 230 V~ - 10 MA - 16 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	235,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 10 mA
- In : 16 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

Environmental product profile

- [Environnemental product sheet n°8 E0013C-EN](#)

CAT. N° 4 115 09



RCCB TX³ - 2P 230 V~ - 30 MA - 25 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	201,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 30 mA
- In : 25 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 10



RCCB TX³ - 2P 230 V~ - 30 MA - 40 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	201,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 30 mA
- In : 40 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 11



RCCB TX³ - 2P 230 V~ - 30 MA - 63 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	234,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 30 mA
- In : 63 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 12



RCCB TX³ - 2P 230 V~ - 30 MA - 80 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	235,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 30 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 19


RCCB TX³ - 2P 230 V~ - 100 MA - 25 A - AC TYPE


Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	208,00

Product characteristics
2-pole - 230 V~
AC type

- Sensitivity : 100 mA
- In : 25 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01575EN-03](#)

CAT. N° 4 115 20

**RCCB TX³ - 2P 230 V~ - 100 MA - 40 A - AC TYPE**


Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	208,00

Product characteristics**2-pole - 230 V~****AC type**

- Sensitivity : 100 mA
- In : 40 A
- Number of modules : 2

General characteristics**RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types**

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)

 **Installation & technical data**

- [F01575EN-03](#)

CAT. N° 4 115 21


RCCB TX³ - 2P 230 V~ - 100 MA - 63 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	208,00

Product characteristics
2-pole - 230 V~
AC type

- Sensitivity : 100 mA
- In : 63 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)


Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 22



RCCB TX³ - 2P 230 V~ - 100 MA - 80 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	207,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 100 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 29



RCCB TX³ - 2P 230 V~ - 300 MA - 25 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	200,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 300 mA
- In : 25 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 30



RCCB TX³ - 2P 230 V~ - 300 MA - 40 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	200,00

Product characteristics

2-pole - 230 V~

AC type

- Sensitivity : 300 mA
- In : 40 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 31


RCCB TX³ - 2P 230 V~ - 300 MA - 63 A - AC TYPE


Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	201,00

Product characteristics
2-pole - 230 V~
AC type

- Sensitivity : 300 mA
- In : 63 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01575EN-03](#)

CAT. N° 4 115 32


RCCB TX³ - 2P 230 V~ - 300 MA - 80 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	201,00

Product characteristics
2-pole - 230 V~
AC type

- Sensitivity : 300 mA
- In : 80 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [VDE - 40041193](#)
- [QC / CB - CB FR_700536](#)
- [QC / CB - CB FR_704741](#)
- [VDE - 40041193](#)


Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 52



RCCB TX³ - 2P 230 V~ - 10 MA - 16 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	235,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 10 mA
- In : 16 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation



Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741



Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 59


RCCB TX³ - 2P 230 V~ - 30 MA - 25 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	197,00

Product characteristics
2-pole - 230 V~
A type

- Sensitivity : 30 mA
- In : 25 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741


Installation & technical data

- F01575EN-03

CAT. N° 4 115 60


RCCB TX³ - 2P 230 V~ - 30 MA - 40 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	198,00

Product characteristics
2-pole - 230 V~
A type

- Sensitivity : 30 mA
- In : 40 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741


Installation & technical data

- [F01575EN-03](#)

CAT. N° 4 115 61


RCCB TX³ - 2P 230 V~ - 30 MA - 63 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	236,00

Product characteristics
2-pole - 230 V~
A type

- Sensitivity : 30 mA
- In : 63 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041196](#)
- [OC / CB - CB FR_700536](#)
- [OC / CB - CB FR_704741](#)

 **Installation & technical data**

- [F01575EN-03](#)

CAT. N° 4 115 62



RCCB TX³ - 2P 230 V~ - 30 MA - 80 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	233,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 30 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 115 64



RCCB TX³ - 2P 230 V~ - 100 MA - 25 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	205,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 100 mA
- In : 25 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation



Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)



Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741



Installation & technical data

- F01575EN-03

CAT. N° 4 115 65



RCCB TX³ - 2P 230 V~ - 100 MA - 40 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	203,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 100 mA
- In : 40 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 115 66



RCCB TX³ - 2P 230 V~ - 100 MA - 63 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	203,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 100 mA
- In : 63 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 115 67



RCCB TX³ - 2P 230 V~ - 100 MA - 80 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	204,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 100 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 115 74



RCCB TX³ - 2P 230 V~ - 300 MA - 25 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	202,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 300 mA
- In : 25 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 115 75

**RCCB TX³ - 2P 230 V~ - 300 MA - 40 A - A TYPE**


Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	201,00

Product characteristics**2-pole - 230 V~****A type**

- Sensitivity : 300 mA
- In : 40 A
- Number of modules : 2

General characteristics**RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types**

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

 **Installation & technical data**

- [F01575EN-03](#)

CAT. N° 4 115 76



RCCB TX³ - 2P 230 V~ - 300 MA - 63 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	202,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 300 mA
- In : 63 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 115 77



RCCB TX³ - 2P 230 V~ - 300 MA - 80 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,39
Weight (g)	201,00

Product characteristics

2-pole - 230 V~

A type

- Sensitivity : 300 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- VDE - 40041196
- OC / CB - CB FR_700536
- OC / CB - CB FR_704741

Installation & technical data

- F01575EN-03

CAT. N° 4 117 07


RCCB TX³ - 4P 400 V~ - 30 MA - 25 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	339,00

Product characteristics
4-pole 400 V~

- Neutral on right-hand side

AC type

- Sensitivity : 30 mA
- In : 25 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [VDE - 40041193](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)


Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 08


RCCB TX³ - 4P 400 V~ - 30 MA - 40 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	338,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

AC type

- Sensitivity : 30 mA
- In : 40 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 09



RCCB TX³ - 4P 400 V~ - 30 MA - 63 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	364,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

AC type

- Sensitivity : 30 mA
- In : 63 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 10

RCCB TX³ - 4P 400 V~ - 30 MA - 80 A - AC TYPE


Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	364,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

AC type

- Sensitivity : 30 mA
- In : 80 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 17


RCCB TX³ - 4P 400 V~ - 100 MA - 25 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	337,00

Product characteristics
4-pole 400 V~

- Neutral on right-hand side

AC type

- Sensitivity : 100 mA
- In : 25 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)


Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 18


RCCB TX³ - 4P 400 V~ - 100 MA - 40 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	337,00

Product characteristics
4-pole 400 V~

- Neutral on right-hand side

AC type

- Sensitivity : 100 mA
- In : 40 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 19



RCCB TX³ - 4P 400 V~ - 100 MA - 63 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	337,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

AC type

- Sensitivity : 100 mA
- In : 63 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 20



RCCB TX³ - 4P 400 V~ - 100 MA - 80 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	337,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

AC type

- Sensitivity : 100 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 27


RCCB TX³ - 4P 400 V~ - 300 MA - 25 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	331,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

AC type

- Sensitivity : 300 mA
- In : 25 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 28


RCCB TX³ - 4P 400 V~ - 300 MA - 40 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	331,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

AC type

- Sensitivity : 300 mA
- In : 40 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 29


RCCB TX³ - 4P 400 V~ - 300 MA - 63 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	331,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

AC type

- Sensitivity : 300 mA
- In : 63 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)
- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 30


RCCB TX³ - 4P 400 V~ - 300 MA - 80 A - AC TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	332,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

AC type

- Sensitivity : 300 mA
- In : 80 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041193](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)
- [VDE - 40041193](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 64



RCCB TX³ - 4P 400 V~ - 30 MA - 25 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	333,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 30 mA
- In : 25 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 65



RCCB TX³ - 4P 400 V~ - 30 MA - 40 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	338,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 30 mA
- In : 40 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [OC / CB - CB FR_705078](#)
- [OC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 66


RCCB TX³ - 4P 400 V~ - 30 MA - 63 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	368,00

Product characteristics
4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 30 mA
- In : 63 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)


Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)


Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 67



RCCB TX³ - 4P 400 V~ - 30 MA - 80 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	367,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 30 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 74



RCCB TX³ - 4P 400 V~ - 100 MA - 25 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	333,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 100 mA
- In : 25 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 75



RCCB TX³ - 4P 400 V~ - 100 MA - 40 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	334,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 100 mA
- In : 40 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 76



RCCB TX³ - 4P 400 V~ - 100 MA - 63 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	334,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 100 mA
- In : 63 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)

CAT. N° 4 117 77


RCCB TX³ - 4P 400 V~ - 100 MA - 80 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	333,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

A type

- Sensitivity : 100 mA
- In : 80 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 84


RCCB TX³ - 4P 400 V~ - 300 MA - 25 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	333,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

A type

- Sensitivity : 300 mA
- In : 25 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 85


RCCB TX³ - 4P 400 V~ - 300 MA - 40 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	332,00

Product characteristics
4-pole 400 V~


- Neutral on right-hand side

A type

- Sensitivity : 300 mA
- In : 40 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041196](#)
- [QC / CB - CB_FR_705078](#)
- [QC / CB - CB-FR_700757](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 86


RCCB TX³ - 4P 400 V~ - 300 MA - 63 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	332,00

Product characteristics
4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 300 mA
- In : 63 A
- Number of modules : 2

General characteristics
RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

 **Installation & technical data**

- [F01576EN-03](#)

CAT. N° 4 117 87



RCCB TX³ - 4P 400 V~ - 300 MA - 80 A - A TYPE

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	333,00

Product characteristics

4-pole 400 V~

- Neutral on right-hand side

A type

- Sensitivity : 300 mA
- In : 80 A
- Number of modules : 2

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types

- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information

- [Description page \(p.054\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40041196](#)
- [QC / CB - CB FR_705078](#)
- [QC / CB - CB-FR_700757](#)

Installation & technical data

- [F01576EN-03](#)