

CAT. N° 4 035 74



MCB TX³ 6000 - 1P - 230/400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 028,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 75



MCB TX³ 6000 - 1P - 230/400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 018,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 76



MCB TX³ 6000 - 1P - 230/400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 015,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 77


MCB TX³ 6000 - 1P - 230/400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 027,00

Product characteristics
Single pole 230/400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 1

General characteristics
MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

 **Installation & technical data**

- [F01569EN-01](#)

CAT. N° 4 035 78



MCB TX³ 6000 - 1P - 230/400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 059,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 79



MCB TX³ 6000 - 1P - 230/400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 340,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 80



MCB TX³ 6000 - 1P - 230/400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 344,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 40 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 81



MCB TX³ 6000 - 1P - 230/400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 404,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 82



MCB TX³ 6000 - 1P - 230/400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	10
Volume (dm ³)	1,635
Weight (g)	1 429,00

Product characteristics

Single pole 230/400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 1

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 84



MCB TX³ 6000 - 1P+N 230 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 036,00

Product characteristics

Single pole + neutral 230 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [AENOR - 030/002306](#)
- [OC / CB - IT-20864](#)
- [VDE - 40039791](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 85



MCB TX³ 6000 - 1P+N 230 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 034,00

Product characteristics

Single pole + neutral 230 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 86



MCB TX³ 6000 - 1P+N 230 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 037,00

Product characteristics

Single pole + neutral 230 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 87



MCB TX³ 6000 - 1P+N 230 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 044,00

Product characteristics

Single pole + neutral 230 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 88


MCB TX³ 6000 - 1P+N 230 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 052,00

Product characteristics
Single pole + neutral 230 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 2

General characteristics
MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

 **Installation & technical data**

- [F01569EN-01](#)

CAT. N° 4 035 89



MCB TX³ 6000 - 1P+N 230 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 394,00

Product characteristics

Single pole + neutral 230 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 035 90



MCB TX³ 6000 - 1P+N 230 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 392,00

Product characteristics

Single pole + neutral 230 V~

- C curve
- Nominal rating In : 40 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 04



MCB TX³ 6000 - 2P - 230/400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 024,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 05



MCB TX³ 6000 - 2P - 230/400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 014,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 06



MCB TX³ 6000 - 2P - 230/400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 014,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 07



MCB TX³ 6000 - 2P - 230/400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 031,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 08



MCB TX³ 6000 - 2P - 230/400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 061,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 09


MCB TX³ 6000 - 2P - 230/400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 000,00

Product characteristics
2-pole 230/400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 2

General characteristics
MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation
 **Catalogue pages & additional information**

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

 **Agreements & certificates of conformity**

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

 **Installation & technical data**

- [F01569EN-01](#)

CAT. N° 4 036 10



MCB TX³ 6000 - 2P - 230/400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 339,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 40 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 11



MCB TX³ 6000 - 2P - 230/400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 414,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 12



MCB TX³ 6000 - 2P - 230/400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	5
Volume (dm ³)	1,635
Weight (g)	1 418,00

Product characteristics

2-pole 230/400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 2

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 14



MCB TX³ 6000 - 3P 400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	310,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 15



MCB TX³ 6000 - 3P 400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	312,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 16



MCB TX³ 6000 - 3P 400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	307,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 17



MCB TX³ 6000 - 3P 400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	312,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 18



MCB TX³ 6000 - 3P 400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	324,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 19



MCB TX³ 6000 - 3P 400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	406,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 20



MCB TX³ 6000 - 3P 400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	403,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 40 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 21



MCB TX³ 6000 - 3P 400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	429,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 22



MCB TX³ 6000 - 3P 400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,521
Weight (g)	430,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 3

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 24



MCB TX³ 6000 - 4P 400 V~ - 6 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	411,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 6 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 25



MCB TX³ 6000 - 4P 400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	413,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 26



MCB TX³ 6000 - 4P 400 V~ - 16 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	410,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 16 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 27



MCB TX³ 6000 - 4P 400 V~ - 20 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	417,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 28



MCB TX³ 6000 - 4P 400 V~ - 25 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	430,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 25 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 29



MCB TX³ 6000 - 4P 400 V~ - 32 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	546,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 32 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 30



MCB TX³ 6000 - 4P 400 V~ - 40 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	541,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 40 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [AENOR - 030/002306](#)
- [QC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 31



MCB TX³ 6000 - 4P 400 V~ - 50 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	572,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 50 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)

CAT. N° 4 036 32



MCB TX³ 6000 - 4P 400 V~ - 63 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

Pack (number of units)	1
Volume (dm ³)	0,701
Weight (g)	572,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating In : 63 A
- Number of modules : 4

General characteristics

MCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Compatible with prong-type supply busbars
- Breaking capacity:
 - 6000 - IEC 60898-1 - 230/400 V~
 - 6 kA - IEC 60947-2 - 230/400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
- Do not accept add-on modules

Documentation

Catalogue pages & additional information

- [Description page \(p.053\)](#)
- [Dimensions of din-rail equipment](#)

Agreements & certificates of conformity

- [VDE - 40039791](#)
- [OC / CB - IT-20864](#)

Installation & technical data

- [F01569EN-01](#)