

IP 55 AIR CONDITIONED FLOOR STANDING CABINET



The Easycab range of Door standing cabinet IP 55 with 2000/5000/6000W Air Condition is designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with GB/T 19183 and IEC 61969.

FEATURES

- Double wall type design with 2000/5000/6000W Air Condition
- 19" External Cabinet
- Protection grade IP55, effectively prevents rain leakage.
- Front door with Anti-theft Mechanical Lock, Three-Point locking structure to provide reliable protection for cabinets.
- The cabinet comes with two air conditioners for the front and the back door. It can be changed according to the customer's preferences.
- The cabinet is equipped with a dust filter to keep the area dust-free.
- LED bulbs are installed to level up the visibility inside the cabinets.
- Intelligent temperature control system is automatically adjusted according to the temperature in the cabin.

Material	Galvanized sheet
Deg. of Protection	IP 55
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Loading capacity	120Kg, 47U(1500Kg)
Material thickness	Mounting Rails: 2.0mm, Others: 1.0-2.0mm
Operation Temperature	-40°C ~ +55°C
Storage temperature	-40°C ~ +70°C
Input voltage	AC220V
Atmospheric Pressure	54 kPa ~ 101 kPa
Relative Humidity	5%-95%
Total solar radiation intensity	≤1120× (1±10%) W/m ²
Energy efficiency ratio	2.2
Thermal Insulation Performance	Thermal Conductivity <0.472W/(m2.k)
LED Lamp 12 Watt	-48v DC
Communication method	RS 485

IP 55 AIR CONDITIONED FLOOR STANDING CABINET

ACCESSORIES

No.	Item	800wide	Materials	Treatment	Note
1.	Frame	2	2.0mm Galvanized sheet	Powder coating	
2.	Front Door	1	1.0mm Galvanized sheet	Powder coating	With Document Holder
3.	Side Door	2	1.0mm Galvanized sheet	Powder coating	Unremovable
4.	Back Door	1	1.0mm Galvanized sheet	Powder coating	
5.	Lock	1	\	\	Anti-Theft Mechanical Handle Lock
6.	Top cover	1	1.0mm Galvanized sheet	Powder coating	With water proof panel
7.	Door seal	1	Black Rubber	\	
8.	Door knob	1	Galvanized sheet 1.0mm	GE	
9.	Release fastener	6 or 12	Galvanized sheet 1.0mm	Powder coating	H≤ 27U, 6pcs
10.	Bottom panel	1	Galvanized sheet 1.0 mm	Powder coating	
11.	Mounting profile	4	Galvanized sheet = 2.0 mm	Zinc plated	
12.	Plinth	1	Galvanized sheet = 2.0 mm	Powder coating	150 mm

ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
13G6-188822X	18U 800X800 IP 55 Front & Back Metal Door Floor Standing Cabinet with 2x 2000W Air Condition.	18	800x800x1000
13G6-248122X	24U 800X1000 IP 55 Front & Back Metal Door Floor Standing Cabinet with 2x 5000W Air Condition.	24	800x1000x1300
13G6-328822X	32U 800X800 IP 55 Front & Back Metal Door Floor Standing Cabinet with 2x 5000W Air Condition.	32	800x800x1650
13G6-428122X	42U 800X1000 IP 55 Front & Back Metal Door Floor Standing Cabinet with 2x 5000W Air Condition.	42	800x1000x1900
13G6-476B22X	47U 600X1200 IP 55 Front & Back Metal Door Floor Standing cabinet with 2X6000W Air Condition	47	600x1200x2200

X: R2[RAL 7035]

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
13G6-188822X	1 x 1	Fumigation free wooden Pallet + Wooden box	90.0	100.0	1200x1100x950
13G6-248122X	1 x 1	Fumigation free wooden Pallet + Wooden box	95.0	105.0	1500x1000x1200
13G6-328822X	1 x 1	Fumigation free wooden Pallet + Wooden box	100.0	110.0	1900x1100x950
13G6-428122X	1 x 1	Fumigation free wooden Pallet + Wooden box	105.0	115.0	2100x1000x1200
13G6-476B22X	1 x 1	Fumigation free wooden Pallet + Wooden box	300.0	315.0	2400x1400x800