NORDEN®

IP 66 AIR CONDITIONED FLOOR STANDING CABINET



The Easycab range of floor standing cabinet IP66 with 600W Air Condition is designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with GB/T 19183 and IEC 61969.

FEATURES

- Double wall type design with 600W Air Condition
- Bolts are fixed inside, no trace design
- Rain awnings on top
- Bottom wire path, cover with rubber
- Front door with handle lock, extra space for AC if needed
- With 20cm height plinth / IP66 without fans With earthing /with 1 fixed shelf

Material	Galvanized sheet
Deg. of Protection	IP 66
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Loading capacity	800 Kg
Material thickness	Mounting Rails: 2.0mm, Others: 1.5-2.0mm
Operation Temperature	-40°C to +55°C
Relative Humidity	Less than or equal to 95 percent (+35°C)
Atmospheric Pressure	70KPa to 106Kpa

ACCESSORIES

No.	Item	600 wide	800wide	Materials Treatment		Note
1.	Frame	2	2	2.0mm galvanized steel	Powder coating	
2.	Front Door	1	1	1.5mm galvanized steel	Powder coating	With file box
3.	Side Door	2	2	1.5mm galvanized steel	Powder coating	Unremovable
4.	Back Door	1	1	1.5mm galvanized steel	Powder coating	
5.	Lock	1	1	\	\	Handle Lock
6.	Top cover	1	1	1.5mm galvanized steel	Powder coating	With water proof panel
7.	Door seal	1	1	Black Rubber	\	
8.	Door knob	1	1	galvanized steel T=1.5	GE	
9.	Release fastener	\	6 or 12	galvanized steel=1.5	Powder coating	H≤27U, 6pcs
10.	Bottom panel	1	1	galvanized steel=1.5	Powder coating	
11.	Mounting angle	6	6	galvanized steel=1.5	Powder coating	H≤27U, 4pcs
12.	Mounting profile	4	4	galvanized steel=2.0	Zinc plated	
13.	Plinth	1	1	galvanized steel=2.0	Powder coating	L=10 to 20 cm



IP 66 AIR CONDITIONED FLOOR STANDING CABINET

ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
132A-158822X	15U 800 x 800 IP 66 Front and Back Metal Door Air-Conditioned Floor Standing Cabinet	15	800x800x1000
132A-278820X	27U 800 x 800 IP 66 Front Metal Door Air-Conditioned Floor Standing Cabinet	27	800x800x1350
132A-278120X	27U 800 x 1000 IP 66 Front Metal Door Air Conditioned Floor Standing Cabinet	27	800x1000x1350

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)

PACKING INFORMATION

Part Number Packing Qty.		Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
132A-158822X	1 x 1	Carton + Wooden pallet	145	170	870x1000x1160
132A-278820X	1 x 1	Carton + Wooden pallet	120	130	800x800x1400
132A-278120X	1 x 1	Carton + Wooden pallet	130	140	800x1000x1400