

## SINGLE SECTION WALL MOUNT CABINET IP 54



The Easycab range of wall mount cabinet IP54 designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It comply with GB/T 19183 and IEC 61969 standards.

### FEATURES

- The cabinet adopt the single wall type design. It is composed with main body, roof, the rear panel, the side panel and the base.
- Front solid metal door or plexiglass door with black water-proof rubber
- There is a polyurethane joint strip near the protect slot, which is dust proof and waterproof
- The cabinet can adopt 19 inch structure to install cabling equipment, It can be installed on the wall and pole
- Front door with bolt lock
- Bottom wire path with flanges

Material	SPCC cold rolled steel
Degree of protection	IP54
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity powder coating
Loading capacity	30 - 60 KGS.
Material thickness	Mounting profile: 2.0mm, Other: 1.5-2.0mm



## SINGLE SECTION WALL MOUNT CABINET IP 54

### ACCESSORIES

Accessories	Material Of Construction	Surface Coating & Colour	Quantity
Frame	2.0mm SPCC steel	Powder coating	2
Front Door	1.5mm SPCC steel/plexiglass	Powder coating	1
Side	1.5mm SPCC steel	Powder coating	2
Back	1.5mm SPCC steel	Powder coating	1
Lock	\	\	1
Top Cover	1.5mm SPCC steel	Powder coating	1
Door Seal	Black Rubber	\	1
Door Knob	SPCC T=1.5	GE	1
Release fastener	SPCC T=1.5	Powder coating	6 or 12
Bottom Panel	SPCC T=1.5	Powder coating	1
Mounting Profile	SPCC T=2.0	Zincplated Option	4

### ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
131M-156620X	15U 600 x 600 Front metal door single section W/M cabinet IP 54	15	600 x 600 x 770
131M-216620X	21U 600 x 600 Front metal door single section W/M cabinet IP 54	21	600 x 600 x 1030
131M-156610X	15U 600 x 600 Front glass door single section W/M cabinet IP 54	15	600 x 600 x 770
131M-216610X	21U 600 x 600 Front glass door single section W/M cabinet IP 54	21	600 x 600 x 1030

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010), R4(RAL 7032)