

# POE WALL MOUNT INTERCOM TERMINAL



## DESCRIPTION

The NVS-IP100022IC is a PoE wall-mount intercom terminal designed for indoor use, featuring a durable high-grade aluminum panel, IK10 protection, and HD audio. It includes a built-in 3W speaker and microphone for hands-free calling and broadcast reception. The device supports initiating and receiving calls without a server, with offline targets configurable via its web interface. It also allows alarm input/output expansion through an external module and supports cross-network segment and router connectivity via a standard RJ45 Ethernet port.

## FEATURES

- ◉ 6mm aluminum anti-stab and tamper-proof panel
- ◉ Built-in 3W speaker and mic with Hands-free call support
- ◉ Line-out for active speaker or earphone
- ◉ Relay I/O for access control or alarm link
- ◉ Supports offline and one-press calls
- ◉ SIP compliant, PoE powered, Remote upgrade enabled


## Specifications

Model	NVS-IP100022IC
Power Supply	DC24V/1A, PoE (IEEE802.3at)
Standby Power Consumption	≤3W
Signal to Noise Ratio	Broadcast Speaker: 81dB Broadcast Line: 88dB Line-in Record out: 82dB
Audio Sampling & Bit Rate	22.05KHz, 16bit, 8kbps~320kbps
Built-in Speaker (Power Output)	3W
Built-in Speaker (Impedance)	8Ω
Built-in Mic	Electret Microphone
Built-in Mic (Sensitivity)	-45dB±3dB
Built-in Mic (Directivity)	Omnidirectional

# POE WALL MOUNT INTERCOM TERMINAL


Harmonic Distortion	<1%
Frequency Response	40Hz~10KHz (WAV)
	50Hz~20KHz (MP3)
Network Interface	10BASE-T/100BASE-TX RJ45
Network protocol	TCP/IP, UDP, ARP, ICMP, IGMP, SIP, HTTP, FTP
Configuartion Method	Web Interface
Mounting Method	Wall Mounted
Installation Environment	Dry Indoor Locations
Operating Temperature	-20°C~+60°C [-4°F~140°F]
Operating Humidity	25%~90%(RH non-condensing)
Body Material	Aluminium Alloy
Colour	Silver
Back Shell Material	Steel
Product Dimension	101x191x46 mm
Product Weight	0.95 Kg

## FRONT PANEL




# POE WALL MOUNT INTERCOM TERMINAL

## CONNECTION DIAGRAM



# POE WALL MOUNT INTERCOM TERMINAL

## Input Connection




### ③ Comprehensive Interface

■ NC	┌──┐	Alarm output (NC: normally closed, COM: COM, NO: normally open)
■ COM	┌──┐	
■ NO	┌──┐	
■ GND	┌──┐	Alarm input 1 (GND: Ground, L1: alarm input1)
■ I1	┌──┐	
■ REC/LINE	┌──┐	Record out/line out interface (REC/LINE: Signal, GND: ground)
■ GND	┌──┐	
■ AUX_IN	┌──┐	Line in interface (AUX_IN: Signal, GNDA: Analog ground)
■ GNDA	┌──┐	
■ GND	┌──┐	
■ T/R	┌──┐	Three-color door light interface (GND: Ground, T/R: Signal, PWR: Power)
■ PWR	┌──┐	

# POE WALL MOUNT INTERCOM TERMINAL

## DIMENSION

Unit mm



## ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP100022IC	POE WALL MOUNT INTERCOM TERMINAL	01

## ACCESSORIES INFORMATION

Description	Standard Quantity
Power Adaptor (24V/1A)	01
User Manual	01